


SPECIFICATION		DATA	
Material and thickness	Cold roll steel 0.8mm	System power	40W
Diffuser Material	Polycarbonate	Total Lumen	4000LM
Reflector/purity	98%CHINESE	System efficiency	100LM/W
Cross plates Quantity V	10	UGR	<15
Frame Material/color	Metal/White	Beam angel	82
Certificates	CE RoHS EN62471	Driver brand	TRIDONIC/OSRAM/PHILIPS
Class	I	Dimmable	AVAILABLE
IP	IP20	PF	>0.96
Warranty	5 YEARS	THD	<20%
IK	IK05(0.7J)	Flicker free	<10%
Glow wires	850 Degrees	LED Chip brand	SAMSUNG LG
Connector	Linect/Gst18i3	LED PCB board	4PCS
Cut out hole	570x570mm	CRI	>80
External size	595x595mm	LM80 8000 hours	97.9(55degrees)
Weight	4.82KGS	L70/B50 hours	YES
Size	595x595x55mm	IES file available	YES
Box Quantity packaging size	62x61x6cm	LM79	YES
Quantity for 40"HighCube	2800pcs	Low Color Tolerance	ANSI/MacAdam 3
		DC Voltage range	54-150V

EXCELL IP65 40W LED

This luminaire contains built-in LED lamps.

The LED lamps cannot be changed in the luminaire

874/2012



H[m]	D[m]	Max lux	Med lux	Beta=82°	G=0,0 Max not at G
1.00	1.52	2812	1640		
2.00	3.05	703	410		
3.00	4.57	312	182		
4.00	6.10	176	102		
5.00	7.62	112	66		

