



LEVELED



SPECIFICATION		DATA	
Material and thickness	Cold roll steel 0.8mm	System power	30W
Diffuser Material	PMMA	Total Lumen	3161LM
Reflector/purity	System efficiency	103LM/W
Cross plates Quantity V	0	UGR	<16
Frame Material/color	Metal/White	Beam angel	88.6
Certificates	CE RoHS EN62471	Driver brand	TRIDONIC/OSRAM/PHILIPS
Class	I	Dimmable	AVAILABLE
IP	IP40	PF	>0.96
Warranty	5 YEARS	THD	<20%
IK	IK05(0.7J)	Flicker free	<10%
Glow wires	850 Degrees	LED Chip brand	SAMSUNG LG
Connector	Linect/GST18i3	LED PCB board	2PCS
Cut out hole	570x570mm	CRI	>80
External size	595x595mm	LM80 8000 hours	97.9(55degrees)
Weight	4.3KGS	L70/B50 hours	YES
Size	595x595x50mm	IES file available	YES
Box Quantity packaging size	62x61x6cm	LM79	YES
Quantity for 40"HighCube	2800pcs	Low Color Tolerance	ANSI/MacAdam 3
		DC Voltage range	54~150V

LEVELED 30W LED


This luminaire contains built-in LED lamps.

A++
A+
A
B
C
D
E

LED

The LED lamps cannot be changed in the luminaire

874/2012



H[m]	D[m]	Max lux	Med lux	Beta= 88.6°	G=0.0
1.00	2.70	2161	624		
2.00	5.41	540	156		
3.00	8.11	240	69		
4.00	10.81	135	39		
5.00	13.52	86	25		

