



SPECIFICATION	DATA
Material and thickness	Cold roll steel 0.8mm
Diffuser Material	Polycarbonate
Reflector/purity	98%CHINESE
Cross plates Quantity V	44
Frame Material/color	Metal/White
Certificates	CE RoHS EN62471
Class	I
IP	IP20
Warranty	5 YEARS
IK	IK05(0.7J)
Glow wires	850 Degrees
Connector
Cut out hole
External size	1130x150mm
Weight	3.7KGS
Size	1250x150x100mm
Box Quantity packaging size	128x36x34cm 6Pcs
Quantity for 40"HighCube	2450pcs

System power	45W
Total Lumen	4294LM
System efficiency	95LM/W
UGR	<20
Beam angel	95
Driver brand	TRIDONIC/OSRAM/PHILIPS
Dimmable	AVAILABLE
PF	>0.97
THD	<20%
Flicker free	<10%
LED Chip brand	SAMSUNG SEOUL
LED PCB board	2PCS
CRI	>80
LM80 8000 hours	97.9(55degrees)
L70/B50 hours	YES
IES file available	YES
LM79	YES
Low Color Tolerance	ANSI/MacAdam 3
DC Voltage range	54~150V


MAXLUX 45W LED

This luminaire contains built-in LED lamps.

LED

The LED lamps cannot be changed in the luminaire

874/2012



H[m]	D[m]	Max lux	Med lux	Alpha=95°	G=0,0 Max not at G
1,00	2,08	1862	1623		
2,00	4,17	465	751		
3,00	6,25	206	541		
4,00	8,34	116	360		
5,00	10,42	74	180		

