


20W / 2FT / 1900LM
40W / 4FT / 3800LM
50W / 5FT / 4750LM

SPECIFICATION		DATA	
Material and thickness	Cold roll steel 0.8mm	System power	38W
Diffuser Material	PMMA	Total Lumen	4105LM
Reflector/purity	System efficiency	108LM/W
Cross plates Quantity V	0	UGR	<20
Frame Material/color	Metal/White	Beam angel	111.2
Certificates	CE RoHS EN62471	Driver brand	TRIDONIC/OSRAM/PHILIPS
Class	I	Dimmable	AVAILABLE
IP	IP20	PF	>0.96%
Warranty	5 YEARS	THD	<20%
IK	IK05(0.7J)	Flicker free	<10%
Glow wires	850 Degrees	LED Chip brand	SAMSUNG LG
Connector	LED PCB board	4PCS
Cut out hole	CRI	>80
External size	1190x260mm	LM80 8000 hours	97.9(55degrees)
Weight	2.3KGS	L70/B50 hours	YES
Size	1190x210x70mm	IES file available	YES
Box Quantity packaging size	122x46x26cm 6pcs	LM79	YES
Quantity for 40*HighCube	2600pcs	Low Color Tolerance	ANSI/MacAdam 3
		DC Voltage range	54~150V

SOFT 38W LED



This luminaire contains built-in LED lamps.



LED

The LED lamps cannot be changed in the luminaire

874/2012

