



	30W ESS	30W ADV
3000K	3000LM 100LM/W	2850LM 95LM/W
4000K	3180LM 106LM/W	3060LM 102LM/W

SPECIFICATION	DATA		
Material and thickness	Cold roll steel 0.8mm	System power	30W
Diffuser Material	PMMA	Total Lumen	3125LM
Reflector/purity	System efficiency	106LM/W
Cross plates Quantity V	0	UGR	<18
Frame Material/color	Metal/White	Beam angel	112
Certificates	CE RoHS EN62471	Driver brand	TRIDONIC/OSRAM/PHILIPS
Class	I	Dimmable	AVAILABLE
IP	IP20	PF	>0.96
Warranty	5 YEARS	THD	<20%
IK	IK05(0.7J)	Flicker free	<10%
Glow wires	850 Degrees	LED Chip brand	SAMSUNG LG
Connector	Linect/GST1813	LED PCB board	2PCS
Cut out hole	570x570mm	CRI	>80
External size	595x595mm	LM80 8000 hours	97.9(55degrees)
Weight	3.62KGS	L70/B50 hours	YES
Size	595x595x70mm	IES file available	YES
Box Quantity packaging size	62x61x8cm	LM79	YES
Quantity for 40*HighCube	1800pcs	Low Color Tolerance	ANSI/MacAdam 3
		DC Voltage range	54~150V

WINGO 30W LED

This luminaire contains built-in LED lamps.

A++
A+
A
B
C
D
E

LED

The LED lamps cannot be changed in the luminaire

874/2012

