




نور عمان




NOOROMAN

ND85

Recessed Downlight

Item	Power	CCT	LM/W	Lumen	Finish	Dimensions
ND85-03-10W	10W LED	3000K	110	1100lm	RAL9016/RAL9005	Ø85x84mm, cutout 75mm
ND85-04-10W	10W LED	4000K	120	1200lm	RAL9016/RAL9005	Ø85x84mm, cutout 75mm
ND85-05-10W	10W LED	5000K	120	1200lm	RAL9016/RAL9005	Ø85x84mm, cutout 75mm
ND85-06-10W	10W LED	6000K	120	1200lm	RAL9016/RAL9005	Ø85x84mm, cutout 75mm
ND85-65-10W	10W LED	6500K	120	1200lm	RAL9016/RAL9005	Ø85x84mm, cutout 75mm



LIGHT TECHNICAL DATA

Light Source : LED
Light Source Included : Yes
Replaceability : Replaceable LED by professional,
Replaceable Control gear by professional
Colour Rendering Index (Ra) : >80
Colour Consistency (SDCM) : 3
Beam Angle (°) : 15, 24, 36
Light sharing : Symmetric
Light Outlet : Direct
Number of Lamps (pcs) : SMD
Life Time : L80 B20 50,000h
Nominal Life Time (h) : 50,000
Emergency: Possible on request
CCT Selection DIP Switch: YES

TECHNICAL DATA

Voltage Interval (V) : AC220-240
Line Frequency (Hz) : 50/60Hz

MEASUREMENT AND INSTALLATION

Operating Environment : Indoor
IP Degree of Protection : IP44
Installation : Recessed mounted

OPERATION AND CONNECTION

Driver Included : Yes
PF : ≥ 0.50
Operating Temperature (°C) : -20...+45
Max. Tc (°C) : 65
Dimmable : Optional - DALI / 1-10V

CONSTRUCTION

Body : Die-cast Aluminium
Diffuser : PMMA lens



INSTALLATION

