




نور عمان



NOOROMAN

iSeal_{WP}

Weatherproof Light

Item	Power	CCT	LM/W	Lumen	Finish	Dimensions
N453L601LED2840	25W LED	4000K	96	2400lm	RAL9006	600x107x75mm
N453L601LED2850	25W LED	5000K	96	2400lm	RAL9006	600x107x75mm
N453L601LED2865	25W LED	6500K	96	2400lm	RAL9006	600x107x75mm
N453L1152LED3840	47W LED	4000K	96	4500lm	RAL9006	1152x107x75mm
N453L1152LED3850	47W LED	5000K	96	4500lm	RAL9006	1152x107x75mm
N453L1152LED3865	47W LED	6500K	96	4500lm	RAL9006	1152x107x75mm
N453L1453LED3840	58W LED	4000K	102	5920lm	RAL9006	1450x107x75mm
N453L1152LED3850	58W LED	5000K	102	5920lm	RAL9006	1450x107x75mm
N453L1453LED3865	58W LED	6500K	102	5920lm	RAL9006	1450x107x75mm
N453L1703LED3840	70W LED	4000K	102	7140lm	RAL9006	1700x107x75mm
N453L1703LED3850	70W LED	5000K	102	7140lm	RAL9006	1700x107x75mm
N453L1703LED3865	70W LED	6500K	102	7140lm	RAL9006	1700x107x75mm



LIGHT TECHNICAL DATA

Light Source : LED
Light Source Included : Yes
Replaceability : Replaceable LED by professional,
Replaceable Control gear by professional
Colour Rendering Index (Ra) : >80
Colour Consistency (SDCM) : 3
Beam Angle (°) : 110
Light sharing : Symmetric
Light Outlet : Direct
Number of Lamps (pcs) : 1
High efficacy LED modules
Life Time : L80 B20 50,000h
Nominal Life Time (h) : 50,000
Emergency: Possible on request

TECHNICAL DATA

Voltage Interval (V) : 220...240
Line Frequency (Hz) : 50, 60

OPERATION AND CONNECTION

Driver Included : Yes
Driver Model : Constant Current Driver
Driver Manufacturer : VS,OSRAM,TRIDONIC
Operating Temperature : -25...+55
Max. Tc (°C) : 75
Dimmable : Optional - DALI / 1-10V

CONSTRUCTION

Body : Extruded Aluminium, Die-cast Aluminium
Diffuser : Polycarbonate

MEASUREMENT AND INSTALLATION

Operating Environment : Indoor/Outdoor
IP Degree of Protection : IP65 IK07
Installation : Surface mounted, Pipe Clamp mounted, Wall mounted, Suspension

