




نور عمان




NOOROMAN

LINE-S

LED Batten Light

Item	Power	CCT	LM/W	Lumen	Finish	Dimensions
LINE-S 63140	18W LED	4000K, 5000K, 6500K	122	2200lm	RAL9003	L1160xW109xH85mm
LINE-S 63150	22W LED	4000K, 5000K, 6500K	123	2720lm	RAL9003	L1160xW109xH85mm
LINE-S 63160	30W LED	4000K, 5000K, 6500K	123	3690lm	RAL9003	L1160xW109xH85mm
LINE-S 63240	35W LED	4000K, 5000K, 6500K	122	4300lm	RAL9003	L1160xW159xH85mm
LINE-S 63250	42W LED	4000K, 5000K, 6500K	125	5270lm	RAL9003	L1160xW159xH85mm
LINE-S 63260	58W LED	4000K, 5000K, 6500K	125	7290lm	RAL9003	L1160xW159xH85mm



LIGHT TECHNICAL DATA

Light Source : LED
Light Source Included : Yes
Replaceability : Replaceable LED by professional,
Replaceable Control gear by professional
Colour Rendering Index (Ra) : >95
Colour Consistency (SDCM) : 3
Beam Angle (°) : 110
Light sharing : Symmetric
Light Outlet : Direct
Number of Lamps (pcs) : 1
Life Time : L90 B10 50,000h
Nominal Life Time (h) : 50,000
Emergency: Possible on request
RG: 0

TECHNICAL DATA

Voltage Interval (V) : 220...240
Line Frequency (Hz) : 50, 60

MEASUREMENT AND INSTALLATION

Operating Environment : Indoor
IP Degree of Protection : IP54
Installation : Surface mounted

OPERATION AND CONNECTION

Driver Included : Yes
Driver Model : Constant Current
Operating Temperature : -20...+55
Max. Tc (°C) : 85
Dimmable : Optional - DALI / 1-10V

CONSTRUCTION

Body : Polycarbonate
Diffuser : Polycarbonate

