



NL-AA Backlit Grille



Thickness

Only 49mm, saving shipping cost.



Diffuser

UGR<19,
No yellowing risk without LGP.



Backplane

Anti-bending, Integrated forming process Smooth corner.



Frame

21mm width 6063 Aluminum,
Seamless, no light leakage.




Lens

Mitsubishi PMMA lens,
no yellowing and burst.




Driver

External driver, DC connetor,
easy to installation and be replaced by
0-10V dimming driver, Dali dimming
driver or other brand drivers



CCT changeable available



	NL6060-AA	90°	IP20	UGR<19	CRI≥80	TP(b)	AC 200-240V
	Watt	Size(AxBxCmm)		Lumen(±5%)			
	36W	595x595x49		100lm/w			
	NL6262-AA	90°	IP20	UGR<19	CRI≥80	TP(b)	AC 200-240V
	Watt	Size(AxBxCmm)		Lumen(±5%)			
	36W	620x620x49		100lm/w			
	NL30120-AA	90°	IP20	UGR<19	CRI≥80	TP(b)	AC 200-240V
	Watt	Size(AxBxCmm)		Lumen(±5%)			
	36W	1195x295x49		100lm/w			
	NL60120-AA	90°	IP20	UGR<19	CRI≥80	TP(b)	AC 200-240V
	Watt	Size(AxBxCmm)		Lumen(±5%)			
	36W	1195x595x49		100lm/w			